











PIN ASSIGNMENT:

| RJ45 | DB15M |
|---|---|
| 1 | BLUE |
| 2 | ORANGE |
| 3 | BLACK |
| 4 | RED |
| 5 | GREEN |
| 6 | YELLOW |
| 7 | BROWN |
| 8 | WHITE |

OPEN/SHORT TEST: 100% TEST
INSULATION: 5M.
RoHS Compliant

| No. | Description | Q'ty |
|---|---|---|
| 6 | SCREWS：L=37.0mm(±0.5mm,NICKEL PLATED) | 2PCS |
| 5 | ABS SHELL：BEIGE COLOR | 1PCS |
| 4 | CONNECTOR:RJ45 F | 1PCS |
| 3 | CONNECTOR:DB 15M（BLACK INSULATOR,NICKEL PLATED） | 1PCS |
| 2 | Terminal：DB 15M（GOLD FLASH） | 8PCS |
| 1 | UL 1007 #26 WIRE L=85mm | 8PCS |

| | |
|---|---|
| Dat | 2012 / 10 / 30 |
| Unit | mm |
| Projection | |
| Rev | A |

DELOCK
we move the world

| | |
|---|---|
| Title: | Adapter Sub-D 15 Pin male > RJ45 female assembly kit |
| Item no. | 65432 |
| Barcode | 4043619654321 |
| File No. | 88090 |