




REV	ECRN	DATE
1	NEW PRODUCTION	20150512
2	NEW PRODUCTION	20180314




模具编号：P-38

NOTES:


- 1.ELECTRICAL TEST:100%OPEN,SHORT&MIS WIRE TEST.
- 2.CONTACT RESISTANCE:0.5ohm,
- 3.INSULATOR RESISTANCE:5M ohm.
- 4.HIGH VOLTAGE:DC 300V 0.01sec.
- 5.MUST BE ROHS COMPLIANT.

TTL--PCB

TOP



BOTTOM



PIN WIRING

P1	P2
1 RED(VCC 5V)	4(VCC)
2 ORANGE	1(TXD)
3 YELLOW	2(RXD)
4 GREEN	
5 BLACK	3(GND)
6 BROWN	

⑨	B.04035M.0N04R	CONNECTOR	AUDIO PLUG 3.5MM*6.0 4-POLE SHELL NICKEL PLATING PLASTIC: BLACK	1	PCS
⑧	I.150200.0306R	PE BAG	200*150*0.04MM PE BAG PRINTED BLACK"USB TO TTL 3.3V AUDIO PLUG 3.5MM	1	PCS
⑦	F.0501B0.0100R	TUBE	φ5.5*20mm HEAT TUBE COLOR BLACK	1	PCS
⑥	I.000001.0400R	TIE	TIE BLACK L=70MM	1	PCS
⑤	C.045P01.0100R	MOLDING	PVC 45P BLACK	12.5	G
④	C.000000.0000R	MOLDING	PE	2.5	G
③	J.000008.0500R	TIN WIRE	TIN WIRE OD:0.8MM	3.5	G
②	B.01004M.0N06R	CONNECTOR	TTL-PCB(3.3V) USB A/M CONNECTOR PLASTIC: BLACK	1	PCS
①	A.009X01.0400R	CABLE	UL2464 28AWG(7/0.12BC)*4C PVC JACKET COLOR:BLACK OD=3.5±0.1mm L=1780MM	1	PCS
NO.	PART NO	ITEM	DESCRIPTION	Q' TY	UNIT

**DELICK®**  
we move the world

Title: Converter USB 2.0 male > TTL 3.5 mm 4 pin stereo jack male 1.8m (3.3 V)

Date	2018 / 02 / 01	Item no.	83779
Unit	mm	Barcode	4043619837793
Projection		File No.	88203
Rev	A		