



#### PIN ASSIGNMENT

P1		P2	
1	8	5	(WHITE/ORANGE)
2	8	3	(ORANGE)
3	8	4	(WHITE/GREEN)
6	8	8	(GREEN)
4	8	6	(BLUE)
5	8	7	(WHITE/BLUE)
7	8	1	(WHITE/BROWN)
8	8	2	(BROWN)
S		S	

#### NOTES:

1. PIN ASSIGNMENT SEE TO WIRE LIST.
2. ELECTRICAL TEST CONDITION:
  - (a). 100% OPEN, SHORT & MISWIRE TEST,
  - (b). INSULATOR RESISTANCE: 10 MOHM MIN.  
DC 300V 0.01 SEC.
  - (c). CONTACT RESISTANCE: 3 OHM MAX.

Item	L (mm)	A (mm)
84922	1000	±20
84923	2000	±30
84924	3000	±50
84925	5000	±100
84926	10000	±150

4	OVERMOLD BLACK PVC 45P MA-001	
3	M12 8 PIN MALE BLACK PBT WITH NICKLE PLATED SHELL	
2	8P8C PLUG WITH NICKLE PLATED SHELL	
1	(54/0.06TA*1P+T)*4+TB OD: 6.5 MM BLACK PVC JACKET UL20276	
NO.	Description	P/N

Date	2019 / 01 / 30	<b>DELOCK®</b> we move the world	
Unit	mm	Title Cable RJ45 plug to M12 plug 8 pin A-coded Cat.5e SFTP	
Projection		Item no.	84922 84923 84924 84925 84926
Rev	A	File No.	88286