

Delock 5.25" Mobile Rack for 4 x 2.5" SATA / SAS HDD / SSD 12 Gb/s

Description

This mobile rack by Delock can be installed into a free 5.25" bay of a desktop PC and enables the operation of up to four 2.5" SATA or SAS hard drives.

Quick change of hard drives

Due to the special mechanism, the hard disks can be exchanged quickly and easily. For example, data backups can be taken and stored in a safe place.

Protection against theft

Each of the four removable frames is provided with a separate lock. Thus, the hard disks and data can be protected against theft and misuse.

Operation with SATA controller

This mobile rack by Delock can also be used on motherboards with SATA controllers.

With the Delock item 83320, the Mini SAS HD port on the mobile rack can be connected to four free SATA ports of the motherboard and allows the use of up to four SATA HDDs.

Note

- It is not possible to use SAS hard disks with a SATA controller.



Item no. 47233

EAN: 4043619472338

Country of origin: China

Package: White Box

Technical details

- Connectors:
 - internal:
 - 4 x SFF-8680 female
 - external:
 - 1 x Mini SAS HD SFF-8643 female
 - 1 x SATA 15 pin power connector
- Suitable for 2.5" SATA / SAS HDD / SSD:

HDD height up to 15 mm
supports 5 V HDD / SSD

- Data transfer rate:
SATA up to 6 Gb/s
SAS up to 12 Gb/s
- Mobile rack with key lock for each bay
- 4 x LED indicator for power and access
- Robust aluminum housing
- 2 x fan 35 x 35 mm at the back side
- Fan speed control in two steps
- OS independent, no driver installation necessary

System requirements

- PC with one free 5.25" bay
- PC with one SAS or SATA controller
- Power supply with SATA 15 pin receptacle
- 1 Mini SAS HD cable

Package content

- 5.25" mobile rack
- 4 x 2.5" mobile rack inner tray
- 2 x keys
- 8 x rack screws
- 16 x hard drive screws
- User manual

Images



General

| | |
|-----------------------------|--|
| Form factor: | 5.25" |
| Suitable for data medium: | 2.5" SSD or HDD height up to 15.0 mm |
| Supported operating system: | OS independent, no driver installation necessary |

Interface

| | |
|-----------|--|
| External: | 1 x 36 pin SFF-8643 female 1 x 15 Pin SATA Stromanschluss |
| Internal: | 4 x SFF-8680 Buchse |

Technical characteristics

| | |
|---------------------|---------------|
| Data transfer rate: | up to 12 Gbps |
|---------------------|---------------|

Physical characteristics

| | |
|-------------------|--------|
| Housing material: | metal |
| Length: | 151 mm |
| Width: | 146 mm |
| Height: | 42 mm |
| Colour: | black |