

Navilock NL-601US USB 2.0 GPS Receiver

Description

The USB GPS Receiver based on u-blox 6 chipset has a built-in antenna for high sensitivity. You can use this GPS Receiver with a notebook and a suitable routing software for navigation. Due to its compact design it is the ideal companion on every tour.



Item no. 60123

EAN: 4043619601233

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Technical details

- u-blox 6 GPS SuperSense® high performance chipset
- Frequency: L1, 1575.42 MHz, C/A Code: 1.023 MHz
- Accepts the signals of up to 50 satellites at the same time
- Supports AGPS, WAAS, EGNOS and MSAS
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, VTG
- USB specification 2.0
- Baud Rate up to 115200
- UP-DATE Rate: up to 5 Hz
- Sensibility max. -162dBm
- LED-indicator for GPS-status
- Operating temperature: -20 °C to +60 °C
- Cold start in about 25 sec.
- Hot start in about 1 sec.
- Positioning accuracy:
2.5 m CEP (Circular Error Probable) and
2 m CEP with SBAS
- Dimension (LxWxH): 65.5 mm x 23 mm x 11 mm

System requirements

- Linux ex Kernel 2.6, Windows 98SE/ME/2000/XP/Vista/7/8/10, Windows Mobile 2003/5/6
 - PC or Notebook with a free USB Port
 - For devices with OTG function and optional OTG adapter: Windows 10
-

Package content

- USB GPS receiver
 - USB extension cable
 - Driver CD
 - User manual on CD ROM
-

Images

