

# Delock USB to SATA 6 Gb/s Converter with USB Type-C™ or USB Type-A connector

# **Description**

This Delock converter can be connected via USB-C<sup>™</sup> or USB Type-A interface to a PC or laptop. Thus a 2.5" SATA HDD or SSD with a 22 pin SATA interface can be used.

# **Extensive connectivity**

Due to the specially designed adapter, the Delock converter can be quickly and easily connected to the USB Type-A socket. Thus, it can be easily connected to new devices with USB Type-C<sup>TM</sup> female and older devices that only have a USB Type-A connector. The adapter is located directly on the cable and therefore it cannot be lost.



# Item no. 61042

EAN: 4043619610426 Country of origin: China Package: Retail Box

#### **Technical details**

- Connectors:
  - 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) USB Type-C™ male
  - 1 x SATA 6 Gb/s 22 pin receptacle

#### Adapter:

- 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) USB Type-C™ female
- 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A male
- Chipset: Asmedia ASM1153e
- Suitable for 2.5" SATA HDD / SSD
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate up to 5 Gb/s
- Plug & Play
- Length incl. connectors: ca. 30 cm

#### System requirements

- Android 11.0 or above
- Chrome OS



- Linux Kernel 5.13 or above
- Mac OS 12.2.1 or above
- Windows 8.1/8.1-64/10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C<sup>™</sup> port or with a free Thunderbolt<sup>™</sup> 3 port or
- A free USB Type-A port

# **Package content**

- Converter
- Cover cap
- User manual

# **Images**









# General

Suitable for data medium:	2.5"
Supported operating system:	Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Linux Kernel 5.13 or above Mac OS 12.2.1 or above Android 11.0 or above

# Interface

Connector 1:	1 x USB 5 Gbps USB Type-C™ male
Connector 2:	1 x SATA 6 Gb/s 22 pin receptacle

# **Technical characteristics**

Chipset:	Asmedia ASM1153E
Data transfer rate:	5 Gbps

# **Physical characteristics**