

Navilock NL-303P serial MD6 GPS Receiver

Description

The PDA GPS Receiver based on SiRFstarIII™ Chipset has a built-in antenna for high sensitivity.

The MD6 universal connector enables the connection of optional USB or serial connecting cables. You can use this GPS Receiver on a Notebook or PDA with suitable routing software for navigation.



Item no. 61423

EAN: 4043619614233

Country of origin: Taiwan,
Republic Of China

Package: Retail Box

Special features

Please note that the SiRFstarIII chipset used here has reached the end of its production cycle. This receiver is delisted in the next few weeks.

Technical details

- SiRFstarIII™ high performance and low power chipset
- GPS receiver with MD6 Navilock plug
(USB or serial cable are optional available)
- Accepts the signals of up to 20 satellites at the same time
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, GLL and VTG
- 4800 – 38400 Baud
- Waterproof housing
- Magnatic, non-slip on the bottom
- LED-indicator for GPS-status
- Cold start in about 42 sec.
- Warm start in about 38 sec.
- Hot start in about 1 sec.
- Dimension (LxWxH): 65 mm x 45 mm x 22 mm
- Cable lenght: 1.50 m

System requirements

- Windows CE/98/ME/2000/XP/Vista/7
- MD6 connection cable

Package content

- PDA GPS Receiver
- Driver CD
- User manual

Images

