

# Delock Converter SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) to SATA 6 Gbps incl. power supply

## Description

This Delock converter can be connected via USB Type-A interface to a PC or laptop. Thus, different SATA devices with 22 pin SATA interface can be operated. The included power supply can be used for 3.5" SATA HDDs or optical drives.



**Item no. 62486**

EAN: 4043619624867

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type Micro-B female
  - 1 x DC jack
  - 1 x SATA 6 Gb/s 22 pin receptacle
- Chipset: Asmedia
- For SATA HDD, SATA SSD, optical drive etc.
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate up to:
  - SuperSpeed 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- LED indicator
- Plug & Play

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
  - inside:  $\varnothing$  ca. 2.5 mm
  - outside:  $\varnothing$  ca. 5.5 mm
  - length: ca. 9.5 mm

## System requirements

- Linux Kernel 3.2 or above
- Mac OS 10.8 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

## Package content

- Converter USB - SATA 6 Gb/s
- Cable SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A male to SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type Micro-B male, length ca. 0.8 m
- External power supply
- User manual

## Images

