

Navilock Connection Cable MD6 female serial > 3.5 mm 3 pin stereo jack male 90° TTL (5 V) 52 cm

Description

The connection cable by Navilock converts the serial signals for all MD6 receivers to TTL 5 V signals. Compatible with TTL/CMOS is this interface suitable for GPIO, UART, Controller and CPU.



ca. 52 cm

Item no. 62885

EAN: 4043619628858

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x MD6 female >
 - 1 x 3.5 mm 3 pin stereo jack male 90°
- Chipset: ASIX ZT3221LEEY
- Data transfer: unidirectional
- Cable gauge: 28 AWG
- Voltage: 5 V
- Cable colour: black
- Length incl. connectors (L): ca. 52 cm


System requirements

- A Navilock serial MD6 GNSS receiver

Package content

- Connection cable for GNSS receiver
 - Navilock support CD
-

Images



General

Style:	angled 90°
--------	------------

Interface

connector:	1 x MD6 jack
Connector 1:	1 x 3.5 mm 3 pin stereo jack male

Technical characteristics

Chipset:	ASIX ZT3221LEEY
Voltage:	5 V

Physical characteristics

Cable colour:	black
Cable length incl. connector:	52 cm