

Navilock Connection Cable MD6 female serial > 2.5 mm 4 pin stereo jack male 90° LVTTL (3.3 V) 52 cm

Description

The connection cable by Navilock converts the serial signals universally for all MD6 receivers to LVTTL 3.3 V signals. Compatible with LVTTL/CMOS is this interface suitable for GPIO, UART, Controller and CPU.



ca. 52 cm

Item no. 62924

EAN: 4043619629244

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x MD6 female >
 - 1 x 2.5 mm 4 pin stereo jack male 90°
- Chipset: ASIX ZT3221LEYY
- Data transfer: bidirectional
- Voltage: 3.3 V
- Cable colour: black
- Length incl. connectors (L): ca. 52 cm

System requirements

- A Navilock serial MD6 GNSS receiver

Package content

- Connection cable for GNSS receiver
- Navilock support CD

Images



General

Style:	angled 90°
--------	------------

Interface

connector:	1 x MD6 jack
Connector 1:	1 x 2.5 mm 4 pin stereo jack male

Technical characteristics

Chipset:	ASIX ZT3221LEEY
Voltage:	3.3 V

Physical characteristics

Cable colour:	black
Cable length incl. connector:	52 cm