

# Delock Adapter USB Type-C™ male > HDMI female (DP Alt Mode) 4K 60 Hz with PD function

### Description

This Delock adapter is suitable for the connection of a HDMI monitor to a computer with USB-C<sup>TM</sup> interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like Macbook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt<sup>TM</sup> 3 interface. The adapter has a USB Type-C<sup>TM</sup> Power Delivery port. This allows the laptop to be charged while the adapter is in use.

**Delock Monitor Adapter (Video)** 



#### Item no. 62988

EAN: 4043619629886 Country of origin: China Package: Retail Box

#### **Technical details**

• Connectors:

Input:

1 x USB Type-C™ male

1 x USB Type-C™ Power Delivery female (optional for power supply)

Output:

- 1 x HDMI-A 19 pin female
- Chipset: VIA VL100 + Parade PS176
- DisplayPort 1.2 and High Speed HDMI with Ethernet (HEC) specification
- Resolution up to 4096 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of audio and video signals
- Audio formats: 8-channel LPCM, compressed audio and HBR audio format up to 24 Bit audio sample size and 192 kHz sample rate
- Supports 3D displays
- Supports HDCP 1.4 and 2.2
- Charging power: max. 60 W, 20 V @ 3 A
- USB bus powered
- Plug & Play
- · Housing material: aluminium



- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- · Colour: dark grey

#### **System requirements**

- Android 6.0 or above
- Chrome OS
- iPad Pro (2018)
- Linux Kernel 4.3 or above
- Mac OS 10.12 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- Windows 10 Mobile
- PC or laptop with a free USB Type-CTM port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

#### **Package content**

USB-C™ to HDMI adapter

#### **Images**













#### General

Function:	Plug & Play
Specification:	DisplayPort 1.2 High Speed HDMI with Ethernet HDCP 1.4 HDCP 2.2
Supported operating system:	Android 6.0 or above Chrome OS Linux Kernel 4.3 or above Mac OS 10.12 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018)

#### Interface

Output:	1 x HDMI-A female
Input:	1 x USB Type-C <sup>TM</sup> female (power supply) 1 x USB Type-C <sup>TM</sup> male

# **Technical characteristics**

Chipset:	Parade PS176 VIA VL100
Maximum screen resolution:	4096 x 2160 @ 60 Hz
Signal transmission:	video audio

# **Physical characteristics**

Ferrite core:	1 x
Housing material:	Aluminium



# **DATASHEET**

Cable length:	20 cm
Connector finishing:	nickel-plated
Colour:	dark grey