

Delock Adapter USB Type-C™ male to DisplayPort female (DP Alt Mode) 8K 30 Hz

Description

This adapter by Delock is suitable for the connection of a DisplayPort monitor to a computer with USB-C™ interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface.



Item no. 63312

EAN: 4043619633128

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x USB Type-C™ male
 - 1 x DisplayPort female
- Chipset: VIA VL100
- DisplayPort 1.4 specification
- Resolution up to 7680 x 4320 @ 30 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- USB bus powered
- Plug & Play
- Connectors: gold-plated
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- Colour: black

System requirements


- Android 6.0 or above

- Chrome OS
- iPad Pro (3rd Generation) or above
- Linux Kernel 4.3 or above
- Mac OS 10.12 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- Windows 10 Mobile
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ to DisplayPort adapter

Images



General

Function:	Plug & Play
Specification:	DisplayPort 1.2
Supported operating system:	Android 6.0 or above Linux Kernel 4.3 or above Mac OS 10.12 or above Windows 10 32-Bit Windows 10 64-Bit Windows 10 Mobile Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018)

Interface

Output:	1 x DisplayPort female
Input:	1 x USB Type-C™ male

Technical characteristics

Chipset:	VIA VL100
Maximum screen resolution:	4096 x 2160 @ 60 Hz
Signal transmission:	video audio

Physical characteristics

Ferrite core:	1 x
Cable length:	20 cm
Connector finishing:	gold-plated
Colour:	black