

Delock Front Panel 3.5" USB 5 Gbps 1 x USB Type-C™ + 2 x USB Type-A + SD and Micro SD slot

Description

This front panel by Delock can be installed into a free 3.5" bay of a computer. It has two USB 5 Gbps Type-A and one USB 5 Gbps Type-C port. It will be connected to the motherboard internally via a pin header male port.

Integrated Card Reader

In addition, the hub with integrated card reader expands the PC by an SD and a Micro SD slot.



Item no. 64058

EAN: 4043619640584 Country of origin: China Package: Retail Box

Technical details

Connectors:

external:

1 x USB 5 Gbps USB Type-C™ female

2 x USB 5 Gbps Type-A female

1 x SD slot

1 x Micro SD slot

internal:

1 x 19 pin USB pin header female port on the cable

1 x SATA 15 pin power connector

- Chipset: VIA VL817, Genesys Logic GL3224
- Data transfer rate up to:

SuperSpeed 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

- The Card Reader supports following memory cards:
 - 1. Slot Secure Digital

SD, SD3.0 UHS-I, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0



- 2. Slot Micro Secure Digital MicroSD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro
- Cable data:
 - 1 x 19 pin USB pin header female cable, length ca. 54 cm (without connectors)
- 3.5" metal frame
- Colour: black
- Hot Swap, Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free 3.5" bay
- Motherboard with a free 19 pin USB 5 Gbps pin header male
- Power supply with SATA 15 pin receptacle

Package content

- 3.5" front panel
- USB pin header female cable
- Screws
- User manual

Images













General

Form factor:	3.5"
Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 3.3 or above Windows 10 64-Bit Windows 8.1 64-Bit

Interface

External:	1 x Micro SD Slot 1 x SD slot 1 x USB 5 Gbps USB Type-C TM female 2 x USB 5 Gbps Type-A female
Internal:	1 x 19 pin USB 5 Gbps pin header female 1 x SATA 15 pin power connector

Technical characteristics

Data transfer rate: USB 3.2 Gen 1 up to 5 Gbps

Physical characteristics

Housing material:	metal
Length:	102 mm
Width:	95 mm
Height:	26 mm
Colour:	black