

Delock Adapter USB Type-C™ male to 2.5 Gigabit LAN

Description

The adapter by Delock expands a PC or laptop by one network interface via the USB Type-C™ interface. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface.

NBASE-T for higher speed

Modern services and new technologies require higher bandwidths. NBASE-T technology enables speeds of 1 Gbps and 2.5 Gbps with conventional networking cables. The best possible transmission rate is set automatically.



Item no. 65990

EAN: 4043619659906

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male >
 - 1 x 2.5 Gigabit LAN RJ45 jack
- Chipset: Realtek RTL8156
- SuperSpeed USB - 5 Gbps specification
- Data transfer rate:
 - Fast Ethernet up to 100 Mbps (Half/Full Duplex)
 - Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)
 - NBASE-T with up to 2.5 Gbps (Half/Full Duplex)
- Compatible with:
 - IEEE 802.3u: 100BASE-TX
 - IEEE 802.3ab: 1000BASE-T
 - IEEE 802.3bz: 2.5GBASE-T
- Supports Auto MDI-X (automatic detection of standard or crossover network cable)
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation with back-pressure flow control
- Supports 9k Jumbo Frames
- LED indicator for power and activity
- USB bus powered

- Robust metal housing
- Colour: black
- Dimensions (LxWxH): ca. 67.0 x 39.2 x 21.3 mm
- Cable length without connectors: ca. 13.5 cm

System requirements

- Linux Kernel 3.2 or above
- Mac OS 10.7 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port

Package content

- USB Type-C™ 2.5 Gigabit LAN adapter
- User manual

Images



General

| | |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supported operating system: | Linux Kernel 3.2 or above Mac OS 10.7 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit |
| LED indicator: | power and activity |

Interface

| | |
|--------------|---------------------------------|
| Connector 1: | 1 x USB 5 Gbps USB Type-C™ male |
| Connector 2: | 1 x Gigabit LAN RJ45 jack |

Technical characteristics

| | |
|---------------------|--------------------------------------------------------------------------------------------------|
| Chipset: | Realtek RTL8156 |
| Data transfer rate: | Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps Gigabit Ethernet up to 2.5 Gbps |

Physical characteristics

| | |
|-------------------|---------|
| Housing material: | metal |
| Cable length: | 13.5 cm |
| Length: | 67.0 mm |
| Width: | 39.2 mm |
| Height: | 21.3 mm |
| Colour: | black |