


# Delock D-Sub9 female to Terminal Block with Enclosure

## Description

This terminal block adapter by Delock can be used to connect bare wires. Thus the adapter is not only convenient for special industry applications, but also for the hobby area, e.g. railway modelling.



### Protection by enclosure

The plastic enclosure protects the PCB from dirt and damage.

### Strain relief

The integrated strain relief fixes the cable in the enclosure.

**Item no. 66265**

EAN: 4043619662654

Country of origin: Taiwan,  
Republic of China

Package: Zip poly bag

## Technical details

- Connectors:
  - 1 x serial D-Sub 9 female with nuts
  - 1 x 10 pin terminal block
- Pin assignment: 1:1
- Pitch: 3.81 mm
- Useable for a cable gauge from 26 to 18 AWG
- Operating temperature: -20 °C ~ 105 °C
- Dimensions (LxWxH): ca. 51.8 x 34.4 x 21.0 mm

## System requirements

- A free D-Sub 9 pin male

## Package content

- Adapter
- 1 x strain relief
- 2 x locking screws

## Images



## Interface

|              |                                     |
|--------------|-------------------------------------|
| Connector 1: | 1 x serial Sub-D 9 female with nuts |
| Connector 2: | 1 x 10 pin terminal block           |

## Technical characteristics

|                        |                 |
|------------------------|-----------------|
| Operating temperature: | -20 °C ~ 105 °C |
|------------------------|-----------------|

## Physical characteristics

|                  |             |
|------------------|-------------|
| Pitch distance:  | 3.81 mm     |
| Conductor gauge: | 26 - 18 AWG |
| Length:          | 51.8 mm     |
| Width:           | 34.4 mm     |
| Height:          | 21.0 mm     |