

# Delock Professional Computer Podcasting Microphone with XLR connector and 3 pin stereo jack male + adapter cable for Smartphone and Tablet

### Description

This professional condenser microphone by Delock can be used for high-quality voice and vocal recordings.

#### **Optimal recordings**

The microphone has a high-quality **16 mm condenser chip** and a **cardioid polar pattern** (**unidirectional**) and therefore ideally captures the sound. Due to high power, low self-noise and precise performance, even the finest sounds are recorded crystal clear.

#### Good windscreen

Due to the included windscreen, the recording quality is further optimized. Disturbing wind noises are optimally filtered.

#### **Multifunctional application**

It can be connected to any PC or laptop via the detachable XLR to 3 pin stero jack cable. With the included 4 pin Y-adapter cable, it can also be connected to a tablet or smartphone.

#### Stable & non-slip stand

The metal stand with rubber feet ensures that the microphone stands stable on the table. The microphone holder can be adjusted in a 180° angle as required. The table stand can be easily folded and transported when needed.



#### Item no. 66640

EAN: 4043619666409 Country of origin: China Package: Retail Box

#### **Technical details**

- Connector: 1 x XLR plug
- · Cable:
  - 1 x XLR jack >
  - 1 x 3.5 mm 3 pin stereo jack male
- Y-Adapter:
  - 1 x 3.5 mm 4 pin stereo jack male (CTIA standard) >



1 x 3.5 mm 3 pin stereo jack female microphone

1 x 3.5 mm 3 pin stereo jack female headset

• Directivity: unidirectional

• Sensitivity: -38 dB +/- 3 dB

• Frequency range: 30 Hz - 16 kHz

• Signal-to-noise ratio (SNR): ca. 70 dB

• Self-Noise: max. 16 dBA

• Sound pressure level (SPL): max. 120 dB

• Cable length: ca. 2.5 m

Colour: blackVoltage: 1.5 V

# **System requirements**

• A free stereo port 3.5 mm

## Package content

- XLR microphone
- XLR to stereo jack cable
- Y-adapter cable
- Windscreen
- Microphone holder
- Table stand

## **Images**











# Interface

| connector:   | 1 x XLR Male                      |
|--------------|-----------------------------------|
| Connector 1: | 1 x XLR jack                      |
| Connector 2: | 1 x 3.5 mm 3 pin stereo jack male |

# **Technical characteristics**

| Frequency range:          | 30 Hz - 16 kHz  |
|---------------------------|-----------------|
| Voltage:                  | 1,5 V           |
| Sensibility:              | -38 dB +/- 3 dB |
| Signal noise ratio (SNR): | ca. 70 dB       |
| Directivity:              | uni-directional |

# **Physical characteristics**

| Housing material: | metal |
|-------------------|-------|
| Cable length:     | 2.5 m |
| Colour:           | black |