

# Delock DisplayPort Flat Ribbon Cable 8K 60 Hz 1 m

## Description

This cable by Delock is used to connect devices with a DisplayPort interface, such as monitors or TVs, to a PC or a laptop.

#### 8K resolution and HDR support

By supporting a maximum bandwidth of **32.4 Gbps**, content up to **8K Ultra HD** (7680 x 4320 @ 60 Hz) resolution can be displayed. Due to the **HDR** support colours are realistically displayed with impressive depth, brightness and contrast are optimally reproduced.



1 m

#### Item no. 81005

EAN: 4043619810055 Country of origin: China

Package: Box

#### **Technical details**

- Connectors:
  - 2 x DisplayPort male
- DisplayPort 1.4 specification
- Downwards compatible to DisplayPort 1.3, 1.2 and 1.1
- Pin 20 not connected
- Cable gauge:
  - 30 AWG data line
  - 28 AWG power line
- Cable size: ca. 2.3 x 13 mm
- Copper conductor
- · Contacts gold-plated
- Connector finishing: gold-plated
- · Transmission of audio and video signals
- Data transfer rate up to 32.4 Gbps
- Resolution up to:

Display with DSC support:

7680 x 4320 @ 60 Hz

3840 x 2160 @ 240 Hz

Display without DSC support:

7680 x 4320 @ 30 Hz





3840 x 2160 @ 120 Hz

(depending on the system and the connected hardware)

- Supports Display Stream Compression 1.2 (DSC)
- Supports HDR10
- Supports HDCP 1.4 and 2.3
- Supports HBR3 (8.1 Gbps) data rate
- Up to 32 audio channels for speakers
- Up to 1536 kHz audio sampling rate
- Supports colour sampling in 4:4:4, 4:2:2 and 4:2:0 format
- Colour: black
- Length incl. connectors: ca. 1 m

# **Package content**

• DisplayPort cable

## **Images**





#### General

Specification: HDCP 1.4

DisplayPort 1.4

HDR10 HDCP 2.3

## Interface

Connector 1: 1 x DisplayPort male

Connector 2: 1 x DisplayPort male

## **Technical characteristics**

Data transfer rate: 32.4 Gb/s

Maximum screen resolution: 7680 x 4320 @ 60 Hz

# **Physical characteristics**

Pin finishing:	gold-plated
Conductor material:	copper
Conductor gauge:	30 AWG data line 28 AWG power line
Length:	1 m
Colour:	black