

Delock Converter USB 2.0 male > TTL 3.5 mm stereo jack 1.8 m (3.3 V)

Description

This USB 2.0 Serial-TTL converter by Delock is due to its wide temperature range most suitable for industrial applications. It can be used for e.g. level converter, GPS-modules, interface controller, micro controller etc.



1,8 m

Item no. 83114

EAN: 4043619831142

Country of origin: China

Package: Retail Box

Technical details

- Connector: USB 2.0 Serial-TTL male > 3.5 mm stereo jack (1. GND, 2. RXD, 3. TXD)
- Chipset: FTDI 232RL
- Cable gauge: 26 AWG
- Temperature range: -20°C to +80°C
- No-load current: 70 uA
- Converter: 5 V / 15 mA (VCC, GND)
- Compatible to UHCI / OHCI / EHCI controller
- LVTTTL 3.3 V (data) / 4 mA or HighLevel 12 mA
- Data transfer rate up to 3 Mbps
- Databit: 7 or 8
- Stopbits: 1 or 2
- Parity: none, space character, straight, unequal, mark
- Flow control: software XON/XOFF or hardware RTS/CTS
- FIFO: 128 Byte – RX
256 Byte – TX
- Cable length: ca. 1.80 m

System requirements

- Linux Kernel 2.6 or above
- Mac OS 10.5 or above
- Windows CE 4.2/5.0/6.0
- Windows XP/XP-64/Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- Converter USB 2.0 Serial-TTL
- Driver CD
- User manual

Images

