


Delock USB4™ 40 Gbps Coaxial Cable 0.8 m

Description

This USB4™ cable by Delock enables the connection of various devices, such as smart phones, monitors, external enclosures and docking stations, via a USB Type-C™ or Thunderbolt™ 3 port of a PC or laptop. The cable supports the transfer of USB as well as DisplayPort and PCI Express data.



The cable enables data transfer rates up to 40 Gbps when connecting USB4TM-compatible devices. Of course, USB 3.2 or USB 2.0 devices can also be connected.

Connect DisplayPort monitors

The Delock cable supports DisplayPort 1.4a as well as DisplayPort 2.0 Alternate Mode, enabling the connection of DisplayPort monitors with a screen resolution up to 8K 60 Hz.

USB Power Delivery (USB PD 3.0) support up to 100 watt

Supports the USB Power Delivery 3.0 standard, which allows connected devices to be powered with up to 100 W (20 V / 5 A).



0,8 m

Item no. 86979

EAN: 4043619869794 Country of origin: China Package: Retail Box

Technical details

- Connectors:
 - 1 x USB4™ 40 Gbps (Gen 3x2) USB Type-C™ male >
 - 1 x USB4[™] 40 Gbps (Gen 3x2) USB Type-C[™] male
- USB-IF certified cable
- Downwards compatible to USB 3.2, USB 2.0 and Thunderbolt™ 3
- Chipset: Cypress E-Marker
- · Cable type: coaxial
- Cable gauge:
 - 30 AWG data line
 - 24 AWG power line
- Contacts gold-plated
- Cable diameter: ca. 4.8 mm
- Data transfer rate up to 40 Gbps



• Display resolution up to:

7680 x 4320 @ 60 Hz

5120 x 2880 @ 120 Hz

3840 x 2160 @ 240 Hz

(depending on the system and the connected hardware)

- Supports HDR10
- Supports HDCP 1.4 and 2.3
- Supports PCI Express 3.0 protocol
- Supports DisplayPort 1.4a protocol
- Supports DisplayPort Alt Mode 2.0
- Dual channel, bi-directional data transfer
- USB Power Delivery (USB PD 3.0) support up to 100 watt (20 V / 5 A)
- · Colour: black
- Length incl. connectors: ca. 80 cm

System requirements

 Device with a free USB Type-C[™] port and DisplayPort alternate mode or with a free Thunderbolt[™] 3 port

Package content

• USB4™ 40 Gbps cable

Images







General

HDCP 1.4
USB Type-C™
DisplayPort 1.4
HDR10
PCI Express 3.0
HDCP 2.3
USB4
USB Power Delivery 3.0

Interface

Connector 1:	1 x USB4 Gen 3x2 Type-C™ male
Connector 2:	1 x USB4 Gen 3x2 Type-C™ male

Technical characteristics

Chipset:	Cypress E-Marker
Data transfer rate:	40 Gbps
Maximum screen resolution:	7680 x 4320 @ 60 Hz
Maximum load:	100 W
Maximum current:	5 A
Data transmission:	Bi-directional
Voltage:	20 V

Physical characteristics

Cable category:	coaxial
Conductor gauge:	30 AWG data line 24 AWG power line
Length:	0.8 m
Colour:	black