

Delock USB Type-C™ Splitter (DP Alt Mode) > 2 x HDMI out 4K 30 Hz

Description

This splitter by Delock is suitable for the connection of two HDMI monitors to a computer with USB-C™ interface and DisplayPort alternate mode support. Two monitors can be operated simultaneously at the outputs.



Note

The product is a Multi-Stream-Transport (MST) hub and supports the extended desktop configuration of Displayport 1.2. When Mac OS is used, the same image is displayed on both ports (mirrored), it is not possible to use both ports independently of each other.

Item no. 87719

EAN: 4043619877195

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
Input: 1 x USB Type-C™ male
Output: 2 x HDMI-A 19 pin female
- Chipset: STDP4320
- DisplayPort 1.2 specification
- Resolution up to 2560 x 1440 @ 60 Hz / 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Functions: Mirrored or Extended (Windows only)
- Transfer of audio and video signals
- USB bus powered
- Colour: black
- Cable length incl. connectors: ca. 25 cm
- Dimensions (LxWxH): ca. 61 x 49 x 11 mm

System requirements

- Windows 8.1/8.1-64/10/10-64/11, Mac ex OS 10.9
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ Splitter (DP Alt Mode)
- User manual

Images



General

Specification:	DisplayPort 1.2
Supported operating system:	Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11

Interface

Output:	2 x HDMI-A female
Input:	1 x USB Type-C™ male

Technical characteristics

Chipset:	STDP4320
Maximum screen resolution:	3840 x 2160 @ 30 Hz

Physical characteristics

Housing colour:	black
Housing material:	Plastic
Cable length incl. connector:	25 cm
Length:	61 mm
Width:	49 mm
Height:	11 m