

# Delock PCI Express x16 Card to 2 x internal NVMe M.2 Key M

## Description

This PCI Express card by Delock expands the PC by two M.2 slots. Up to two M.2 SSDs in format 2280, 2260, 2242 and 2230 can be connected. With the help of the large heat sink and the fan onboard, sufficient cooling of the M.2 modules is guaranteed.



**Item no. 89961**

EAN: 4043619899616

Country of origin: China

Package: Box

## Technical details

- Connectors:  
internal:  
2 x 67 pin M.2 key M slot  
1 x PCI Express x16, V3.0
- Chipset: Asmedia ASM2824
- Interface: PCIe
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Data transfer rate up to 32 Gbps
- Supports NVM Express (NVMe)
- Bootable (one slot - CN1)
- 1 x 40 mm fan for active cooling of the M.2 modules
- 1 x heat sink
- 2 x LED indicator
- Dimensions heat sink (LxWxH): ca. 202 x 95 x 8 mm

---

## System requirements

- Linux Kernel 3.17 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC with one free PCI Express x16 / x32 slot

---

## Package content

- PCI Express card with fan
- Heat sink
- M.2 mounting material
- Screwdriver
- 3 x thermal pad
- User manual

---

## Images



## General

Function:	NVM Express (NVMe) bootable
Supported operating system:	Linux Kernel 3.17 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11
Slot:	PCIe
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

## Interface

Internal:	2 x 67 pin M.2 key M slot 1 x PCI Express x16, V3.0
-----------	--

## Technical characteristics

Chipset:	Asmedia ASM2824
----------	-----------------

## Physical characteristics

Slot bracket:	standard
---------------	----------