

# Delock PCI Express x1 Card to 2 x Serial RS-232 + 1 x Parallel IEEE1284

## Description

The PCI Express card by Delock expands a PC by two external serial ports as well as one external parallel port. Different devices such as scanner, printer, mouse etc. can be connected to this card.



**Item no. 90413**

EAN: 4043619904136

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - external:
    - 2 x serial RS-232 DB9 male (separate rear bracket)
    - 1 x Parallel DB25 female
  - internal:
    - 1 x PCI Express x1, V1.1
- Chipset: WCH CH384L
- Operating temperature: -40 °C ~ 85 °C
- Relative humidity: 0 - 95 % (non condensing)
- Dimensions (LxWxH): ca. 79 x 59 x 11 mm
- Serial specification:
  - Data transfer rate up to 460.8 Kbps
  - FIFO: 256 byte
  - Compatible with 16C950 UART
- Parallel specification:
  - Data transfer rate up to 1.5 Mbps
  - FIFO: 256 byte
- Supports SPP, Byte and ECP mode

---

## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC with one free PCI Express slot

---

## Package content

- PCI Express card
- Slot bracket
- 3 x low profile bracket
- Driver CD
- User manual

---

## Images



## General

|                             |  |
|-----------------------------|--|
| Specification:              | RS-232 (EIA / TIA)<br>PCIe 1.1<br>SPP, EPP, ECP  |
| Supported operating system: | Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 7 32-Bit<br>Windows 7 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit<br>Windows 11 |
| Slot:                       | PCIe   |

## Interface

|           |   |
|-----------|---|
| External: | 1 x parallel port<br>2 x serial RS-232 DB9 plug |
| Internal: | 1 x PCI Express x1, V1.1                        |

## Technical characteristics

|                     |  |
|---------------------|--|
| Chipset:            | WCH CH382L                             |
| Data transfer rate: | up to 460,8 Kbps<br>LPT up to 1.5 MBps |
| FIFO:               | 256 Byte                               |
| UART:               | 16C550<br>16C552<br>16C554             |

## Physical characteristics

|               |                         |
|---------------|-------------------------|
| Slot bracket: | Low Profile<br>standard |
|---------------|-------------------------|