


# Delock PCI Express x16 Card to 8 x internal SFF-8643 NVMe - Low Profile Form Factor

## Description

This PCI Express card by Delock expands the PC by **eight SFF-8643** interfaces. SSDs with e.g. U.2 interface can be connected to these ports by using an optional cable.



**Item no. 90504**

EAN: 4043619905041

Country of origin: China

Package: White Box

## Technical details

- Connectors:
  - 8 x SFF-8643 female
  - 1 x PCI Express x16, V3.0
- Chipset: Broadcom PEX8749
- Data transfer rate up to 32 Gbps
- Supports NVM Express (NVMe)
- Bootable, ex UEFI version 2.3.1
- 1 x LED indicator
- Humidity: 15 ~ 90 %
- Operating temperature: 5 °C ~ 50 °C
- Storage temperature: -25 °C ~ 70 °C

## System requirements

- Linux Kernel 3.18.37 or above
- Windows 8.1/8.1-64/10/10-64
- Windows Server 2019

- PC with one free PCI Express x16 / x32 slot

---

## Package content

- PCI Express card
- Low profile bracket
- User manual

---

## Images



## General

Function:	Bootable, ex UEFI 2.3.1 NVM Express (NVMe)
Supported operating system:	Linux Kernel 3.18.37 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2019
LED indicator:	1 x

## Interface

Internal:	1 x PCI Express x16, V3.0 8 x SFF-8643 female
-----------	--

## Technical characteristics

Chipset:	Broadcom PEX8749
Operating temperature:	5 °C ~ 50 °C