

# Delock PCI Express x1 Card to 4 x external USB Type-A female SuperSpeed USB (USB 3.2 Gen 1)

## Description

The PCI Express card by Delock expands a PC by **four external USB 3.2 Gen 1 ports**. Different USB devices such as docking stations, card reader, external enclosure etc. can be connected.

### 10 Watt output power per port

The card requires no additional power supply and can still supply **2 A at each port**. Thus, a total of 8 A can be achieved when all ports are used.



**Item no. 90509**

EAN: 4043619905096

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - external: 4 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
  - internal: 1 x PCI Express x1, V2.0
- Chipset: Renesas D720201
- Data transfer rate up to:
  - SuperSpeed 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- Electrical power per port: max. 10 watt (5 V / 2 A)
- Bootable
- Operating temperature: 0 °C ~ 40 °C
- Storage temperature: -10 °C ~ 70 °C
- Relative humidity: 10 - 90 % (non condensing)

## System requirements

- Linux Kernel 3.18 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free PCI Express slot

---

## Package content

- PCI Express card USB 3.2 Gen 1
- 1 x screw
- User manual

---

## Images



## General

Supported operating system:	Linux Kernel 3.18 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
-----------------------------	--

## Interface

External:	4 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
Internal:	1 x PCI Express x1, V2.0

## Technical characteristics

Chipset:	Renesas D720201
----------	-----------------

## Physical characteristics

Slot bracket:	standard
---------------	----------